



WORKER PRO+

HARNESS 1124

- Patented attachment webbing loops in front
- Designed to fit women as well
- Ergonomic support belt for positioning

A patented fall protection harness developed for a broad spectrum of fall protection requirements. The focus of the harness design is on ergonomics and comfort. It's flexible and has great adjustment possibilities, thus it enables both women and men to achieve a customized fit.

SEGMENTS


- ✓ Pitch roof work
- ✓ MEWPs

ARTICLES

012200143 Cresto, Worker Pro+, one size		
---	--	--

OVERVIEW

The design of the harness and the adjustable shoulder straps provide optimal user fitting in terms of size and comfort. Making the harness "one-size", it enables users from approximately 165 cm to 195 cm in height to fit the harness quite nicely. The patented attachment webbing loops are located at waist height to keep the lanyard/rope out of the way as much as possible, and to give the user a free field of operation, as well as not putting pressure against the chest while working and climbing. In the event of a fall the loops move up to the chest providing a high attachment point, positioning the body correctly in a fall. Same basis design as harness 1123, equipped with a support belt.







SPECIFICATION

PRODUCT PROPERTIES

Front A-point	Textile sliding angled loop >15kN. Not for static work.
Chest buckles	Quick buckles in steel with stainless components Strength >20kN
Back A-point	Galvanized steel 50 mm >22kN
Side D-rings	Galvanized steel 50 mm >22kN
Leg buckles	Quick buckles in steel with stainless components Strength >20kN
Padding material	Breathable 3-D mesh
Adjustable under load	No
Fall indicator	No
Maximum number of users	1
Maximum load (kg)	140.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	100.0
Material	Polyester

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 358 : 2018, EN 361 : 2004
Notified body	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic


ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Warranty	2+1 year when registered in Inspector
Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	Czech (CS), Danish (DA), Dutch (NL), English (EN), Estonian (ET), Finnish (FI), French (FR), German (DE), Greek (EL), Italian (IT), Norwegian (NO), Slovak (SK), Spanish (ES), Swedish (SV)





IMAGES











