

Reebok

WORK SHOES

EXCEL LIGHT



ARTICLE IB1029

CATEGORY  S1P SRC

SIZES 36 - 47

WIDTH 11

WEIGHT
(half pair, sz 42) 440 GR

METAL FREE No

CERTIFICATION 

UPPER

Microfiber and Nylon Mesh

LINING

Breathable Moisture Wicking Mesh. It gives a higher comfort during the whole working day. Optimal resistance to abrasion

TOE CAP

ALUMINIUM TOE CAP - Reduces weight while maintaining impact protection

ANTI-PERFORATION INSERT

Non-magnetic anti-perforation made of composite materials, 40% lighter and more flexible than a steel blade. It gives a major protection by covering the entire surface of the foot

FOOTBED

MemoryTech Memory Foam Removable Cushion Footbed

OUTSOLE

XL ExtraLight® Fuel, Oil, and Abrasion Resistant EVA Blend with Rubber Heel and Toe Slip Resistant Pads

UPPER

Water Vapour Permeability

mg/cm²*h

≥ 0,8

37,4

Water Vapour Coefficient

mg/cm²

≥ 15

300,6

LINING

Water Vapour Permeability

mg/cm²*h

≥ 2,0

42,6

Water Vapour Coefficient

mg/cm²

≥ 20

340,6

TOE CAP

Impact resistance: clearance under the toecap

mm

≥ 14,0

16,5

Compression resistance: clearance under the toecap

mm

≥ 14,0

16,5

ANTI-PERFORATION INSERT

Penetration resistance (EN ISO 12568:2010)

N

≥ 1.000

≥ 1.000

ELECTRICAL RESISTANCE

wet condition (85% relative humidity)

MΩ

≥ 0,1

25,4

dry condition (30% relative humidity)

MΩ

≤ 1000

151

OUTSOLE

Abrasion resistance: relative volume loss

mm³

≤ 250

24

Flexing resistance: cut growth

mm

≤ 4

1,8

Resistance to fuel oil: volume increase

%

≤ 12

9,34

Energy absorption of seat region

J

≥ 20

27

Slip resistance on

7° Heel

≥ 0,13

0,26

steel ground with glycerine

Flat

≥ 0,18

0,28

Slip resistance on

7° Heel

≥ 0,28

0,55

ceramics ground with detergent

Flat

≥ 0,32

0,66

sheet version 1.2



MANUFACTURED BY WARSON BRANDS USA