

Reebok

WORK SHOES

TRAILGRIP



ARTICLE IB1051

CATEGORY S1P HRO SRC 

SIZES 39 - 47

WIDTH 11

WEIGHT
(half pair, sz 42) 530 GR

METAL FREE No

CERTIFICATION 

UPPER

Leather, Microfiber, and Mesh

LINING

Breathable Moisture Wicking Mesh. It gives a higher comfort during the whole working day. Optimal resistance to abrasion

TOE CAP

ALUMINIUM TOE CAP - Reduces weight while maintaining impact protection

ANTI-PERFORATION INSERT

Non-magnetic anti-perforation made of composite materials, 40% lighter and more flexible than a steel blade. It gives a major protection by covering the entire surface of the foot

FOOTBED

MemoryTech Memory Foam Removable Cushion Footbed

OUTSOLE

DMXRide Cushion Foam Midsole with Slip Resistant Rubber Outsole

Requirements EN ISO 20345:2011

Test results

UPPER

Water Vapour Permeability	mg/cm ² *h	≥ 0,8	3,4
Water Vapour Coefficient	mg/cm ²	≥ 15	37,4

LINING

Water Vapour Permeability	mg/cm ² *h	≥ 2,0	15,0
Water Vapour Coefficient	mg/cm ²	≥ 20	98,5

TOE CAP

Impact resistance: clearance under the toecap	mm	≥ 14,0	15,5
Compression resistance: clearance under the toecap	mm	≥ 14,0	16,5

ANTI-PERFORATION INSERT

Penetration resistance (EN ISO 12568:2010)	N	≥ 1.000	≥ 1.000
--	---	---------	---------

ELECTRICAL RESISTANCE

wet condition (85% relative humidity)	MΩ	≥ 0,1	70
dry condition (30% relative humidity)	MΩ	≤ 1000	450

OUTSOLE

Abrasion resistance: relative volume loss	mm ³	≤ 150	55
Flexing resistance: cut growth	mm	≤ 4	1,5
Resistance to fuel oil: volume increase	%	≤ 12	1
Energy absorption of seat region	J	≥ 20	32
Slip resistance on	7° Heel	≥ 0,13	0,15
steel ground with glycerine	Flat	≥ 0,18	0,19
Slip resistance on	7° Heel	≥ 0,28	0,34
ceramics ground with detergent	Flat	≥ 0,32	0,46

sheet version 1.2



MANUFACTURED BY WARSON BRANDS USA