



EN ISO 20345:2011

ENDURANCE
ROLING BOA®
81374-00L

S3 SRC

Size: 36-48
Weight: 750 gr.

Fit: 11

Working Environment:
 Building, Wood-metal carpentry,
 Mountains, Multipurpose

FEATURES

UPPER
 Grain leather Hydro 1,8-2,0 mm
 Reflex insert
 Full Grain leather Hydro

LINING
 3D Air circulation 320 gr.

ANTISLIP LINING
 DUALMICRO

INSOLE
 Climaction-Fit 337

TOE CAP
 Fiber cap SXT

RESISTANCE TO PERFORATION
 Textile resistant to 3.0 mm nail

TYPE
 Ankle boot

SOLE
PU DUAL-DENSITY SRC
 Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.



SRC (SRA+SRB)

		SOLE 81 PU - PU	
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.52	EN ISO 20344:2011
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.23 0.18	

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermofforming for exceptional comfort.



Protection elements
RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability
dynamicHC control
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
 Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
SOA | **FIT TO GO FURTHER.™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.

