

EN ISO 20345:2011



ENDURANCE
ROTOR BOA®
81375-00L

S3 CI SRC

Size: 36-48
Weight: 800 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Mountains, Cold places



FEATURES

UPPER

Grain leather Hydro 1,8-2,0 mm
Reflex insert
Full Grain leather Hydro

LINING

3D Air circulation 320 gr.
GenuineWool Polar

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

TECHNOLOGIES


Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



Protection elements



Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamicHC control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



SRC (SRA+SRB)



SOLE 81
PU - PU

| | | |
|--|------------------------------------|------|
| SRA CERAMIC + DETERGENT SOLUTION | FLAT ≥0.32 | 0.52 |
| | HEEL (CONTACT ANGLE °) ≥0.28 | |
| SRB STEEL + GLYCEROL | FLAT ≥0.18 | 0.23 |
| | HEEL (CONTACT ANGLE °) ≥0.13 | |

EN ISO 20344:2011

Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



**FIT TO GO
FURTHER™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.

