



EN ISO 20345:2022



RESOLUTE
TENACE BOA
45524-00L

S7S FO HI CI SC HRO SR

Size: 36-48
Weight: 850 gr.

Fit: 11

Working Environment:
Building, Farming and Gardening,
Mountains, Wood-metal
carpentry



FEATURES

UPPER

Full Grain leather Hydro 1,8-2,0 mm
No ladder H.T. Fabric
Reflex insert

LINING

GenuineWool Polar
GenuineWool Polar

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation 2.0

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

TYPE

Half-knee Boot

SOLE

PU-RUBBER VIBRAM ECOSTEP PRO-HRO-SR

Sole with anti-wear scaff cap.
Outsole in VIBRAM RECYCLED (≥30%) rubber, resistant to 300° C by contact (HRO), to acids and oils.
Design with self-cleaning outsole, with SR Antislip standard.

Boa® lace length

L+1 - 100cm Top - 85cm Bottom


TECHNOLOGIES

Removable Insole



The ideal insole in recycled material for footwear with "CI" cold protection. The presence of felt with an "aluminized" film for bottom insulation keeps the foot dry and warm.

Protection elements



Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability



Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.







PU - RUBBER

SOLE 45

SLIP RESISTANCE

EN ISO 20345:2022

BASIC CERAMIC WITH NAILS	FORWARD HEEL SLIP ≥ 0.31	0,45	
	BACKWARD FOREPART SLIP ≥ 0.36	0,47	
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,28	
	BACKWARD FOREPART SLIP ≥ 0.22	0,25	

Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Other



D3O materials are made using a combination of advanced polymer chemistry and cutting-edge science. It absorbs and dissipates energy during and impact, with superior stability, cushioning and anti-fatigue effect.

