



EN ISO 20345:2011



RITMO
MENEITO BOA®
91439-01L

S1P SRC

Size: 35-48
Weight: 520 gr.

Fit: 11

Working Environment:
Finishing-off building, Logistics
and Light Industry, Components
and Automotive, ESD Areas



FEATURES

UPPER

MicroFiber Suede 1,6-1,8 mm
SpiderMesh HT
Digitex Airy
MicroFiber Suede with Pro-tech
SXT light 1,6-1,8 mm

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

TYPE

Sandal

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and
in-between sole with ESD
compound. For use in contact with
sensitive electronic equipment.
Light and comfortable, very
versatile, highly non-slip SRC
Antislip standard.

TECHNOLOGIES

Removable Insole

FIVE 4 FIT

Highly breathable and absorbent
anatomic insole. Multilayer structure
to take advantage of the peculiarities
of each component. Dry and with a
comfortable memory foam "pillow"



Protection elements

ZERO(k)
ANTIPERFORATION

alu-sxt2.0
aluminium

A new aluminium multi-thicknesses
toecap, which delivers a highly
performing protection where needed.
Resistant to impact of over 200J. Non
Metallic anti-perforation insert.
Resistant to over 1100 N with zero
perforation.



Lateral stability

dynamic HC control
technology

Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features



ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other



FIT TO GO
FURTHER™

A patented closing system with a multi
coated stainless steel cable. The
BOA® Fit System delivers micro-
adjustable precision fit, engineered to
perform in the toughest conditions.



SRC (SRA+SRB)



SOLE 91
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.54 0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.29 0.23

EN ISO 20344:2011