


8767 C HF TORX® Zyklop bit socket with 1/2" drive with holding function, TX 27 x 140 mm
Zyklop Accessories, 1/2"



EAN:	4013288183569	Size:	206x44x24 mm
Part number:	05003852001	Weight:	118 g
Article number:	8767 C HF	Country of origin:	CZ
		Customs tariff number:	82079030

- Bit socket (non-impact) for manual or machine tool operations
- The holding function holds screws securely on the tool
- With Take it easy tool finder: colour coding by size
- Knurling on lower end for more grip when used manually.
- Chrome vanadium steel, matt chrome-plated

Bit socket with 1/2" drive and holding function for particularly comfortable screwdriving with reduced risk of losing the screw when feeding it into the workpiece. With Take it easy tool finder with colour coding by size - for quick and easy identification of the required tool .

Web link

https://products.wera.de/en/ratchets_and_accessories_the_zyklop_ratchets_the_zyklop_ratchets_1_2_zyklop_accessories_1_2_8767_c_hf.html

Wera - 8767 C HF
05003852001 - 4013288183569

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Bit sockets with holding function for TORX® screws



The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Acument Intellectual Properties specifications are securely held on the tool!

Take it easy tool finder system



Take it easy tool finder system - with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Manual and machine sockets



The manual and machine sockets can be used both for hand and power tools use (non-impact). Users need just one socket set for all applications.

Bit sockets with holding function for TORX® screws



The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Acument Intellectual Properties specifications are securely held on the tool!

Web link

https://products.wera.de/en/ratchets_and_accessories_the_zyklop_ratchets_the_zyklop_ratchets_1_2_zyklop_accessories_1_2_8767_c_hf.html

Wera - 8767 C HF
05003852001 - 4013288183569

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

8767 C HF TORX® Zyklop bit socket with 1/2" drive with holding function, TX 27 x 140 mm
Zyklop Accessories, 1/2"



Further versions in this product family:

						
		mm	mm		mm	mm
05003830001	pink_241C	23.5	21.5	TX 20	16.4	60.0
05003850001	pink_241C	23.5	101.5	TX 20	16.4	140.0
05003831001	gelb_123C	23.5	21.5	TX 25	16.4	60.0
05003851001	gelb_123C	23.5	101.5	TX 25	16.4	140.0
05003832001	blau_307C	23.5	21.5	TX 27	16.4	60.0
05003852001	blau_307C	23.5	101.5	TX 27	16.4	140.0
05003833001	leuchtorange_152C	23.5	21.5	TX 30	16.4	60.0
05003853001	leuchtorange_152C	23.5	101.5	TX 30	16.4	140.0
05003834001	rot_200C	23.5	21.5	TX 40	16.4	60.0
05003854001	rot_200C	23.5	101.5	TX 40	16.4	140.0
05003835001	gruen_363C	23.5	21.5	TX 45	16.4	60.0
05003855001	gruen_363C	23.5	101.5	TX 45	16.4	140.0
05003836001	cyan_2985C	23.5	21.5	TX 50	21.4	60.0
05003856001	cyan_2985C	23.5	101.5	TX 50	21.4	140.0
05003837001	leuchtpink_232C	23.5	21.5	TX 55	21.4	60.0
05003857001	leuchtpink_232C	23.5	101.5	TX 55	21.4	140.0
05003838001	violett_2735C	23.5	21.5	TX 60	21.4	60.0
05003858001	violett_2735C	23.5	101.5	TX 60	21.4	140.0

Web link

https://products.wera.de/en/ratchets_and_accessories_the_zyklop_ratchets_the_zyklop_ratchets_1_2_zyklop_accessories_1_2_8767_c_hf.html

Wera - 8767 C HF
05003852001 - 4013288183569

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de